





# pierścienie AV

d <sub>1</sub>	○									H				D A N E						
	s	Δ	d <sub>3</sub>	Δ	b	Δ	d <sub>5</sub> min.	$\frac{\Delta}{(kg/1000)}$	d <sub>2</sub>	Δ	m min.	t	n	FN (kN)	FR (kN)	g	FRg (kN)	AN (mm <sup>2</sup> )	K (kN/mm)	n <sub>def.</sub> x1000 (rpm)
10	0.60	-0.05	9.2		1.8		1.0	0.25	9.5		0.70	0.25	0.70	0.62	1.4	1.0	1.0	3.8	5.7	84
12	1.00		11.0		2.1		1.3	0.50	11.5		1.10	0.25	1.10	0.70	4.5	2.4	2.4	4.2	21.6	79
13	1.00		11.9		2.1		1.3	0.56	12.4		1.10	0.30	0.9	0.90	5.5	2.4	2.4	5.4	20.8	64
14	1.00		12.9		2.1		1.3	0.58	13.4		1.10	0.30	1.0	0.97	6.0	2.4	2.4	5.8	19.2	56
15	1.00		13.8	+0.10 -0.36	2.2		1.3	0.66	14.3	-0.11	1.10	0.35	1.0	1.22	6.5	2.4	2.4	7.3	19.3	50
16	1.00		14.7		2.3		1.3	0.72	15.2		1.10	0.40	1.2	1.48	7.0	1.0	2.5	8.9	18.7	45
17	1.00		15.7		2.4		1.3	0.81	16.2		1.10	0.40	1.5	1.57	8.1	1.5	2.6	9.4	18.2	41
18	1.20		16.5		2.6		1.5	1.14	17.0		1.30	0.50	1.5	2.07	14.8	1.5	3.2	12.4	32.6	39
20	1.20		18.5		2.8		1.5	1.43	19.0		1.30	0.50	1.5	2.30	14.6	1.5	3.1	13.8	30.1	32
21	1.20		19.35	+0.13 -0.42	2.8		1.5	1.53	20.0	-0.15	1.30	0.50	1.5	2.42	14.4	1.5	3.1	14.5	29.9	29
22	1.20		20.5		3.0	±0.1	1.5	1.63	21.0		1.30	0.50	1.5	2.53	14.2	1.5	3.1	15.2	29.7	27
23	1.20	-0.06	21.5		3.1		1.5	1.78	22.0		1.30	0.50	1.5	2.66	14.0	1.5	3.1	16.0	29.0	25
24	1.20		22.2		3.2		1.5	1.90	22.9		1.30	0.55	1.6	3.03	14.0	1.5	3.1	18.2	28.8	27
25	1.20		23.2		3.4		1.5	2.10	23.9		1.30	0.55	1.6	3.18	14.1	1.5	3.2	19.1	28.8	25
26	1.20		24.2	+0.21 -0.42	3.5		1.5	2.18	24.9	-0.21	1.30	0.55	1.6	3.30	14.1	1.5	3.2	19.8	28.4	25
28	1.50		25.9		3.8		2.0	3.18	26.6		1.60	0.70	2.1	4.50	28.0	2.0	6.4	27.0	56.0	22
30	1.50		27.9		3.9		2.0	3.58	28.6		1.60	0.70	2.1	4.86	27.5	1.5	6.3	29.2	53.5	19
32	1.50		29.6		4.0		2.0	3.88	30.3		1.60	0.85	2.5	6.25	27.0	2.0	4.7	37.0	52.0	17
34	1.50		31.5		3.5		2.0	3.60	32.3		1.60	0.85	2.5	6.67	26.6	2.0	4.6	40.0	50.5	15
35	1.50		32.2	+0.25 -0.50	4.2		2.0	4.53	33.0		1.60	1.00	2.5	8.00	26.6	2.0	4.6	48.0	50.1	16
38	1.75		34.5		4.5		2.0	5.50	35.8		1.85	1.10	3.3	10.60	42.0	2.0	7.8	64.0	77.0	15
40	1.75		36.5		4.7		2.0	6.49	37.5	-0.25	1.85	1.25	3.8	12.60	42.0	2.0	7.8	75.0	77.0	15
42	1.75		38.5		4.7		2.0	6.51	39.5		1.85	1.25	3.8	13.30	42.0	2.0	7.8	80.0	76.0	13
45	1.75		41.5		4.7		2.0	7.80	42.5		1.85	1.25	3.8	14.30	41.5	2.0	7.8	86.0	75.0	11
47	1.75		43.5	+0.39 -0.90	5.0		2.0	8.09	44.5		1.85	1.25	3.8	15.00	41.0	2.0	7.8	90.0	73.5	10
48	1.75		44.5		5.2	±0.2	2.0	8.48	45.5		1.85	1.25	4.5	15.80	41.0	2.0	7.8	95.0	73.5	10
50	2.00		45.8		5.2		2.5	9.84	47.0		2.15	1.50	4.5	19.20	58.0	2.0	11.6	115.0	108.0	10
55	2.00		50.8		5.8		2.5	11.42	52.0		2.15	1.50	4.5	21.00	58.0	2.5	9.3	126.0	104.0	9
58	2.00		53.8		5.8		2.5	13.00	55.0		2.15	1.50	4.5	22.20	56.0	2.5	9.2	133.0	100.0	8
60	2.00		55.8		5.8		2.5	13.80	57.0		2.15	1.50	4.5	23.00	55.5	2.5	9.1	138.0	99.0	7
65	2.50		60.8		6.0		2.5	20.75	62.0	-0.30	2.65	1.50	4.5	24.80	104.0	2.5	17.6	149.0	187.0	6
70	2.50	-0.07	65.5	+0.46 -1.10	6.5		2.5	23.70	67.0		2.65	1.50	4.5	27.00	103.0	2.5	17.6	162.0	185.0	6
72	2.50		67.5		6.5		2.5	24.70	69.0		2.65	1.50	4.5	27.70	104.0	2.5	18.0	166.0	187.0	6
75	2.50		70.5		6.5		2.5	27.50	72.0		2.65	1.50	4.5	29.20	100.0	2.5	17.7	175.0	182.0	5
80	2.50		74.5		7.0		2.5	28.90	76.5		2.65	1.75	5.3	36.60	96.0	3.0	14.6	220.0	175.0	6
82	2.50		76.5		7.0	±0.3	2.5	29.65	78.5		2.65	1.75	5.3	37.40	100.0	3.0	15.4	225.0	184.0	5
85	3.00		79.5		7.4		3.0	39.50	81.5		3.15	1.75	5.3	38.30	167.0	3.0	25.6	230.0	300.0	5
87	3.00		81.5		7.4		3.0	40.00	83.5		3.15	1.75	5.3	39.20	164.0	3.0	25.5	235.0	297.0	5
90	3.00		84.5		7.4		3.0	41.92	86.5	-0.35	3.15	1.75	5.3	41.70	157.0	3.0	24.8	250.0	288.0	4
95	3.00	-0.08	89.5	+0.54 -1.300	8.0		3.0	47.70	91.5		3.15	1.75	5.3	42.70	152.0	3.5	21.0	256.0	285.0	4
100	3.00		94.5		8.0		3.0	49.92	96.5		3.15	1.75	5.3	45.80	144.0	3.5	20.5	275.0	276.0	4



AV



INDUSTRIAL - INOX sp.j.