




≤ 8mm



> 8mm





Wymiar nominalny		1	1,5	2	2,5	3	3,5	4	4,5	5	6	8	10	12	13
a	max.	0.35	0.45	0.55	0.6	0.7	0.8	0.85	1.0	1.1	1.4	2.0	2.4	2.4	2.4
	min.	0.15	0.25	0.35	0.4	0.5	0.6	0.65	0.8	0.9	1.2	1.6	2.0	2.0	2.0
Stan wolny	max.	1.3	1.8	2.4	2.9	3.5	4.0	4.6	5.1	5.6	6.7	8.8	10.8	12.8	13.8
	min.	1.2	1.7	2.3	2.8	3.3	3.8	4.4	4.9	5.4	6.4	8.5	10.5	12.5	13.5
d1															
d2	~	0.8	1.1	1.5	1.8	2.1	2.3	2.8	2.9	3.4	4.0	5.5	6.5	7.5	8.5
s		0.2	0.3	0.4	0.5	0.6	0.75	0.8	1.0	1.0	1.2	1.5	2.0	2.5	2.5
siła kN		0.7	1.58	2.82	4.38	6.32	9.06	11.24	15.36	17.54	26.04	42.76	70.16	104.1	115.1
	4														
	5														
+/- 0,25	6														
	8														
	10														
	12														
	14														
	16														
	18														
	20														
	22														
	24														
+/- 0,50	26														
	28														
	30														
	32														
	36														
	40														
	45														
	50														
	55														
	60														
	65														
	70														
	75														
	80														
	85														
+/- 0,75	90														
	95														
	100														
	120														
	140														
	160														
	180														
	200														
tolerancja	długość														

**kołki sprężyste ISO 8752
(dawniej DIN 1481)**

dostępność

> 8mm



Wymiar nominalny		14	16	18	20	21	25	28	30	32	35	38	40	45	50
a	max.	2.4	2.4	2.4	3.4	3.4	3.4	3.4	3.4	3.6	3.6	4.6	4.6	4.6	4.6
	min.	2.0	2.0	2.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	4.0	4.0	4.0	4.0
Stan wolny d ₁	max.	14.8	16.8	18.9	20.9	21.9	25.9	28.9	30.9	32.9	35.9	38.9	40.9	45.9	50.9
	min.	14.5	16.5	18.5	20.5	21.5	25.5	28.5	30.5	32.5	35.5	38.5	40.5	45.5	50.5
d ₂	~	8.5	10.5	11.5	12.5	13.5	15.5	17.5	18.5	20.5	21.5	23.5	25.5	28.5	31.5
s		3.0	3.0	3.5	4.0	4.0	5.0	5.5	6.0	6.0	7.0	7.5	7.5	8.5	9.5
siła kN		144.7	171	222.5	280.6	298.2	438.5	542.6	631.4	684	859	1003	1068	1360	1685
	4														
	5														
+/- 0,25	6														
	8														
	10														
	12														
	14														
	16														
	18														
	20														
	22														
	24														
+/- 0,50	26														
	28														
	30														
	32														
	36														
	40														
	45														
	50														
	55														
	60														
	65														
	70														
	75														
	80														
	85														
+/- 0,75	90														
	95														
	100														
	120														
	140														
	160														
	180														
	200														
tolerancja	długość	dostępność													

**kołki sprężyste ISO 8752
(dawniej DIN 1481)**