






**pierścienie G**

d <sub>1</sub>								D A N E		
	s	d <sub>3</sub>	Δ	a max.	b ≈	d <sub>5</sub> min.	 (kg/1000)	d <sub>4</sub>	H (N)	n <sub>det.</sub> x1000 (rpm)
1.5	0.40	1.40	±0.020	1.7	0.7	0.9	0.013	5.1	40	350
2.0	0.60	1.90		1.9	1.0	0.9	0.036	6.0	50	260
2.2	0.60	2.05	±0.025	1.9	1.1	0.9	0.038	6.2	50	270
2.5	0.60	2.35	±0.030	1.9	1.2	0.9	0.045	6.5	60	220
2.8	0.60	2.65	±0.035	2.0	1.3	0.9	0.057	7.0	70	190
3.0	0.60	2.85	±0.040	2.1	1.4	0.9	0.065	7.4	75	170
3.5	0.60	3.30	±0.050	2.3	1.6	1.2	0.081	8.3	90	150
4.0	0.80	3.80	±0.060	2.7	1.8	1.2	0.154	9.6	100	125
4.5	0.80	4.25		2.9	2.0	1.3	0.173	10.5	120	120
5.0	0.80	4.75		2.9	2.2	1.3	0.200	11.0	130	100
5.5	0.80	5.20	±0.075	3.0	2.2	1.3	0.216	11.7	150	90
6.0	1.00	5.70		3.2	2.4	1.4	0.402	12.6	170	81
7.0	1.00	6.70		3.4	2.7	1.4	0.428	14.0	180	63
8.0	1.00	7.70		3.5	3.0	1.4	0.524	15.2	200	52
9.0	1.20	8.65	±0.090	4.7	3.3	2.0	0.808	18.6	230	46
10.0	1.20	9.65		4.7	3.5	2.0	0.944	19.6	250	39
10.5	1.20	10.20		4.0	3.8	1.5	1.100	18.7	260	34
11.0	1.20	10.60		4.8	4.2	2.0	1.208	20.8	280	37
12.0	1.20	11.60		4.8	4.6	2.0	1.454	21.8	300	33
13.0	1.20	12.55		5.3	5.0	2.0	1.750	23.8	320	31
13.8	1.50	13.30	±0.110	5.1	5.4	2.2	2.492	24.8	350	30
14.0	1.50	13.50		5.1	5.4	2.2	2.456	25.0	350	29
15.0	1.50	14.50		5.1	5.6	2.2	2.716	26.4	400	26
16.0	1.50	15.40		5.6	5.8	2.5	2.940	27.8	500	26
17.0	1.75	16.35		6.0	6.2	2.5	4.010	29.5	600	24
18.0	1.75	17.30		6.1	6.6	2.5	4.460	31.4	700	23
20.0	1.75	19.30		6.1	7.1	2.5	5.270	34.4	700	20
22.0	1.75	21.20		6.6	7.4	2.5	6.060	37.0	750	18
24.0	1.75	23.15		6.6	7.8	2.5	7.000	39.8	750	16
25.0	1.75	24.15	±0.130	6.6	8.2	2.5	7.450	41.6	750	15
30.0	1.75	29.00		9.0	9.0	2.5	10.000	48.2	750	12



**G**



**INDUSTRIAL - INOX sp.j.**