





pięście DIN 472 - JS wzmacnione

d ₁	☺									☹				D A N E						
	s	Δ	d ₃	Δ	a max.	b ≈	d ₅ min.	(kg/1000)	d ₂	Δ	m min.	t	n	FN (kN)	FR (kN)	g	FRg (kN)	AN(mm ²)	B	
20	1.50		21.5		4.1	2.4	2.0	1.4	21.0	+0.15	1.60	0.50	1.5	5.4	16.2	1.0	5.8	32	2.25	
22	1.50		23.5		4.8	2.8	2.0	1.9	23.0		1.60	0.50			5.9		18.0		6.1	35
24	1.50		25.9	+0.42	4.9	3.0	2.0	2.0	25.2	+0.21	1.60	0.60	1.8	7.7	21.7		7.2	46	1.56	
25	1.50		26.9	-0.21	4.9	3.1	2.0	2.1	26.2		1.60	0.60			8.0	22.8		7.3	48	1.56
26	1.50		27.9		5.1	3.1	2.0	2.3	27.2		1.60	0.60		8.4	21.6		7.2	50	1.56	
27	1.50	-0.06	29.1		5.1	3.2	2.0	2.4	28.4	+0.25	1.60	0.70	2.1	10.1	20.8	1.0	7.0	60	1.56	
28	1.50		30.1		5.1	3.2	2.0	2.5	29.4		1.60	0.70			10.5		20.8		7.0	63
30	1.50		32.1		5.1	3.3	2.0	2.7	31.4	+0.25	1.60	0.70	2.6	11.3	21.4		7.2	67	1.56	
32	1.50		34.4	+0.50	5.4	3.4	2.0	2.9	33.7		1.60	0.85			14.6	21.4		7.3	87	1.56
34	1.75		36.5	-0.25	5.6	3.7	2.5	4.1	35.7		1.85	0.85		15.4	35.6	1.5	8.6	92	1.36	
35	1.75	-0.07	37.8		5.6	3.8	2.5	4.5	37.0	+0.25	1.85	1.00	3.0	18.8	36.6	1.5	8.7	113	1.36	
37	1.75		39.8		5.8	3.9	2.5	4.7	39.0		1.85	1.00			19.8		36.8		8.8	119
38	1.75		40.8		5.8	3.9	2.5	4.8	40.0	+0.25	1.85	1.00	3.8	22.5	38.3		9.1	123	1.36	
40	2.00		43.5	+0.90 -0.39	5.8	3.9	2.5	5.1	42.5		2.15	1.25			27.0	58.4	2.0	10.9	162	1.31
42	2.00		45.5		5.9	4.1	2.5	5.6	44.5		2.15	1.25		28.4	58.5		11.0	170	1.31	
45	2.00	-0.07	48.5		6.2	4.3	2.5	6.3	47.5	+0.30	2.15	1.25	3.8	30.2	56.5	2.0	10.7	181	1.31	
47	2.00		50.5		6.4	4.4	2.5	6.7	49.5		2.15	1.25			31.4		57.0		10.8	189
50	2.50		54.2		6.5	4.6	2.5	8.8	53.0	+0.30	2.65	1.50	4.5	40.5	95.5		19.0	243	1.57	
52	2.50		56.2		6.7	4.7	2.5	9.9	55.0		2.65	1.50			42.0	94.6		18.8	252	1.57
55	2.50		59.2		6.8	5.0	2.5	10.4	58.0		2.65	1.50		44.4	94.7		19.6	266	1.57	
60	3.00	-0.08	64.2		7.3	5.4	2.5	15.9	63.0	+0.30	3.15	1.50	4.5	48.3	137.0	2.0	29.2	290	2.25	
62	3.00		66.2	+1.10	7.3	5.5	2.5	16.1	65.0		3.15	1.50			49.8		137.0		29.2	299
64	3.00		68.2	-0.46	7.4	5.6	3.0	16.5	67.0	+0.30	3.15	1.50	5.3	51.4	137.0		30.0	308	2.25	
65	3.00		69.2		7.6	5.8	3.0	16.6	68.0		3.15	1.50			51.8	174.0	2.5	30.0	313	1.44
68	3.00		72.5		7.8	6.1	3.0	17.2	71.0		3.15	1.50		54.5	174.0		30.6	327	1.44	
70	3.00	-0.10	74.5		7.8	6.2	3.0	18.0	73.0	+0.35	3.15	1.50	4.5	56.2	171.0	2.5	30.3	337	1.44	
72	3.00		76.5		7.8	6.4	3.0	21.7	75.0		3.15	1.50			58.0		172.0		30.3	346
75	3.00		79.5		7.8	6.6	3.0	22.6	78.0	+0.35	3.15	1.50	5.3	60.0	170.0		30.3	360	1.44	
80	4.00		85.5		8.5	7.0	3.0	33.2	83.5		4.15	1.75			74.6	308.0		56.0	448	2.56
85	4.00		90.5		8.6	7.2	3.5	33.8	88.5		4.15	1.75		79.5	358.0	3.0	55.0	477	1.78	
90	4.00	-0.10	95.5	+1.30	8.6	7.6	3.5	41.3	93.5	+0.35	4.15	1.75	5.3	84.0	354.0	3.0	56.0	504	1.78	
95	4.00		100.5	-0.54	8.8	8.1	3.5	46.7	98.5		4.15	1.75			88.6		347.0		56.0	532
100	4.00		105.5		9.2	8.4	3.5	50.7	103.5	+0.54	4.15	1.75	6.0	93.1	335.0		55.0	559	1.78	
105	5.00		112.0		10.2	8.7	4.0	70.0	109.0		5.15	2.00			112.0	681.0		114.0	672	1.56
110	5.00	-0.12	117.0		10.4	9.0	4.0	81.0	114.0		5.15	2.00		117.0	648.0		111.0	704	1.56	



**DIN 472 - JS
wzmacniony**







INDUSTRIAL - INOX sp.j.

d ₁		○								H										
		s	Δ	d ₃	Δ	a max.	b ≈	d ₅ min.	$\frac{\Delta}{(kg/1000)}$	d ₂	Δ	m min.	t	n	FN (kN)	FR (kN)	g	FRg (kN)	AN (mm ²)	B
115		5.00		122.0		10.5	9.3	4.0	94.0	119.0	+0.54	5.15	2.00	6.0	122.0	639.0	3.0	111.0	735	1.56
120		5.00		127.0		11.2	9.7	4.0	98.0	124.0		5.15	2.00		127.0	618.0		109.0	767	1.56
125		5.00		132.0		11.2	10.0	4.0	102.0	129.0		5.15	2.00		132.0	602.0		109.0	797	1.56
130		5.00		137.0		11.2	10.2	4.0	105.0	134.0		5.15	2.00		138.0	584.0		108.0	829	1.56
135		5.00		142.0		11.2	10.5	4.0	107.0	139.0		5.15	2.00		143.0	559.0		105.0	860	1.56
140		5.00		147.0	+1.50	11.2	10.7	4.0	110.0	144.0		5.15	2.00	6.0	148.0	546.0	3.0	104.0	892	1.56
145		5.00		152.0	-0.63	11.2	10.9	4.0	116.0	149.0	+0.63	5.15	2.00		153.0	525.0		102.0	923	1.56
150		5.00		158.0		12.2	11.2	4.0	131.0	155.0		5.15	2.50	7.5	191.0	509.0		100.0	1198	1.56
155		5.00		164.0		12.2	11.4	4.0	134.0	160.0		5.15	2.50		206.0	506.0	3.5	86.0	1237	1.56
160		5.00		169.0		13.2	11.6	4.0	138.0	165.0		5.15	2.50		212.0	501.0		85.0	1275	1.56
165		5.00	-0.12	174.5		14.2	11.8	4.0	156.0	170.0		5.15	2.50	7.5	219.0	498.0	3.5	84.0	1315	1.56
170		5.00		179.5		14.2	12.2	4.0	175.0	175.0		5.15	2.50		225.0	545.0		92.0	1355	1.56
175		5.00		184.5		14.2	12.7	4.0	188.0	180.0		5.15	2.50		232.0	548.0		92.0	1393	1.56
180		5.00		189.5		14.2	13.2	4.0	207.0	185.0		5.15	2.50		238.0	542.0		91.0	1432	1.56
185		5.00		194.5		14.2	13.7	4.0	213.0	190.0		5.15	2.50		245.0	545.0		92.0	1471	1.56
190		5.00		199.5	+1.70	14.2	13.8	4.0	219.0	195.0	+0.72	5.15	2.50	7.5	251.0	531.0	3.5	90.0	1510	1.56
195		5.00		204.5	-0.72	14.2	13.8	4.0	229.0	200.0		5.15	2.50		258.0	516.0		87.0	1550	1.56
200		5.00		209.5		14.2	14.0	4.0	243.0	205.0		5.15	2.50		265.0	508.0		86.0	1565	1.56



**DIN 472 - JS
wzmocniony**



INDUSTRIAL - INOX sp.j.