


podkładki dystansowe PS - DIN 988

∅		$> \blacksquare < / \Delta$											
		kg/1000											
d	D	0.1 -0.03	0.15 -0.04	0.2 -0.04	0.25 -0.04	0.3 -0.05	0.5 -0.05	1.0 -0.05	1.2 -0.07	1.5 -0.07	2.0 -0.07		
3	6	0.016	0.024	0.032	0.040	0.050	0.083	0.165					
4	8	0.030	0.045	0.060	0.075	0.089	0.148	0.296					
5	10	0.046	0.069	0.092	0.115	0.139	0.231	0.462					
6	12	0.067	0.101	0.134	0.168	0.200	0.333	0.666					
7	13	0.074	0.111	0.148	0.185	0.221	0.369	0.738					
8	14	0.082	0.123	0.164	0.205	0.245	0.408	0.815					
9	15	0.089	0.134	0.178	0.223	0.270	0.445	0.891					
10	16	0.096	0.144	0.192	0.240	0.290	0.481	0.963					
11	17	0.103	0.155	0.206	0.258	0.310	0.515	1.030					
12	18	0.111	0.167	0.222	0.278	0.332	0.555	1.110					
13	19	0.119	0.179	0.237	0.296	0.357	0.595	1.190	1.428				
14	20	0.126	0.189	0.252	0.315	0.378	0.630	1.260	1.512				
15	21	0.133	0.199	0.266	0.333	0.399	0.665	1.330	1.596				
15	22	0.137	0.205	0.274	0.342	0.410	0.683	1.360	1.636				
16	22	0.140	0.210	0.280	0.350	0.420	0.700	1.400	1.680				
17	24	0.177	0.266	0.354	0.443	0.530	0.885	1.770	2.124				
18	25	0.185	0.278	0.370	0.463	0.551	0.925	1.850	2.220				
19	26	0.194	0.291	0.388	0.485	0.584	0.970	1.940	2.328				
20	28	0.236	0.354	0.472	0.590	0.710	1.180	2.360	2.832	3.540			
22	30	0.257	0.386	0.514	0.643	0.770	1.280	2.570	3.084	3.855			
22	32	0.333	0.500	0.666	0.833	1.000	1.660	3.330	3.996	4.995			
25	35	0.370	0.555	0.740	0.925	1.110	1.850	3.700	4.440	5.550			
25	36	0.414	0.621	0.828	1.035	1.240	2.070	4.140	4.968	6.210			
26	37	0.427	0.641	0.854	1.068	1.280	2.130	4.270	5.124	6.400			
28	40	0.503	0.755	1.006	1.258	1.510	2.510	5.030	6.036	7.540			
30	42	0.535	0.803	1.070	1.338	1.600	2.680	5.350	6.420	8.030	10.7		
32	45	0.619	0.929	1.238	1.548	1.860	3.100	6.190	7.430	9.290	12.4		
35	45	0.495	0.743	0.990	1.238	1.490	2.480	4.950	5.940	7.430	9.9		
36	45	0.451	0.677	0.902	1.128	1.350	2.250	4.510	5.410	6.760	9.0		
37	47	0.516	0.774	1.032	1.290	1.550	2.580	5.160	6.190	7.740	10.3		
40	50	0.554	0.831	1.108	1.385	1.690	2.770	5.540	6.650	8.310	11.1		
42	52	0.580	0.870	1.060	1.350	1.730	2.900	5.780	6.930	8.680	11.5		
45	55	0.620	0.930	1.220	1.530	1.850	3.100	6.200	7.440	9.300	12.4		
45	56	0.680	1.020	1.360	1.700	2.040	3.400	6.800	8.160	10.200	13.6		
48	60	0.790	1.180	1.580	1.970	2.370	3.950	7.900	9.480	11.800	15.8		



PS - DIN 988




INDUSTRIAL - INOX sp.j.

∅		$> \square < / \Delta$ \triangle kg/1000										
d	D	0.1 -0.03	0.15 -0.04	0.2 -0.04	0.25 -0.04	0.3 -0.05	0.5 -0.05	1.0 -0.05	1.2 -0.07	1.5 -0.07	2.0 -0.07	
50	62	0.83	1.24	1.66	2.07	2.49	4.15	8.30	9.96	12.40	16.60	
50	63	0.91	1.36	1.82	2.27	2.73	4.55	9.10	10.90	13.60	18.20	
52	65	0.94	1.41	1.88	2.35	2.82	4.70	9.40	11.30	14.10	18.80	
55	68	0.98	1.47	1.96	2.45	2.93	4.90	9.80	11.70	14.70	19.60	
56	70	1.09	1.64	2.18	2.73	3.27	5.45	10.90	13.10	16.40	21.80	
56	72	1.27	1.90	2.54	3.17	3.80	6.35	12.70	15.20	19.00	25.40	
60	75	1.25	1.87	2.50	3.12	3.75	6.25	12.50	15.00	18.70	25.00	
63	80	1.50	2.25	3.00	3.75	4.50	7.50	15.00	18.00	22.50	30.00	
65	85	1.85	2.77	3.70	4.62	5.55	9.25	18.50	22.20	27.70	37.00	
70	90	1.97	2.95	3.94	4.92	5.90	9.85	19.70	23.60	29.50	39.40	
75	95	2.09	3.13	4.18	5.22	6.28	10.50	20.90	25.10	31.40	41.80	
80	100	2.22	3.33	4.44	5.55	6.65	11.10	22.20	26.60	33.30	44.40	
85	105	2.34	3.51	4.68	5.85	7.05	11.70	23.40	28.10	35.10	46.80	
90	110	2.47	3.70	4.94	6.17	7.40	12.40	24.70	29.60	37.10	49.40	
95	115	2.59	3.88	5.18	6.47	7.77	13.00	25.90	31.10	38.90	51.80	
100	120	2.72	4.08	5.44	6.80	8.15	13.60	27.20	32.60	40.80	54.40	
100	125	3.47	5.20	6.94	8.67	10.40	17.30	34.70				
105	130	3.62	5.43	7.22	9.05	10.80	18.10	36.20				
110	140	4.62	6.93	9.22	11.50	13.90	23.10	46.20				
120	150	5.00	7.50	10.00	12.50	15.00	25.00	50.00				
130	160	5.36	8.04	10.70	13.40	16.10	26.80	53.60				
140	170	5.73	8.60	11.50	14.30	17.20	28.50	57.30				
150	180	6.10	9.15	12.20	15.20	18.30	30.50	61.00				
160	190	6.47	9.70	12.90	16.20	19.40	32.30	64.70				
170	200	6.85	10.30	13.70	17.10	20.60	34.30	68.50				



PS - DIN 988



INDUSTRIAL - INOX sp.j.